

Technical Data Sheet

Bondloc BVINYL – Vinyl Plastic

Revised 03.08.10



Bondloc Vinyl Plastic

DESCRIPTION

Bondloc Vinyl Plastic is a clear, brushable nitrile adhesive, developed for the repair of flexible PVC.

APPLICATIONS

Ideal for bonding and repairing soft PVC/Vinyl plastics, inflatable beds, paddling pools, pond liners, tents, artificial leather and seat covers.

INSTRUCTIONS FOR USE

- Ensure all surfaces to be bonded are clean, dry and free from grease, dust and any other contaminants. Lightly abrade to expose clean dry PVC
- Apply adhesive to each substrate.
- Allow the adhesive to dry until there is no transfer onto another surface. The time required will depend on ambient temperature, coat weight and substrate
- Join the two substrates together, taking care not to trap any air
- Consolidate the bond with a small roller, using as much pressure as possible
- Allow 30-45 minutes to dry before use, full strength will be achieved overnight

STORAGE

Bondloc Vinyl Plastic should be stored unopened in a dry condition at a temperature of 5 - 25°C. This will ensure a shelf life of 12 months. Once opened the adhesive will have a limited life.

HEALTH & SAFETY

This technical information sheet does not constitute a Material Safety Data Sheet. Before using this product ensure that you have read and fully understood Bondloc Vinyl Plastic MSDS.

PRESENTATION

Tube.....25ml
Clam pack.....25ml

TECHNICAL FEATURES

Base	Nitrile
Appearance	Transparent
Temperature resistance	-30 - 100°C
Application temperature	5 - 25°C
Viscosity	10,000 cps
Tack life	1 – 3 minutes
Open time	1 minute

PRECAUTIONS: This product and the auxiliary materials normally combined with it are capable of producing adverse health effects ranging from minor skin irritation to serious systemic effects. None of these materials should be used, stored, or transported until the handling precautions and recommendations as stated in the Material Safety Data Sheets (MSDS) for this and all other products being used are understood by all persons who will work with the product. Warranty: All products purchased from or supplied by Bondloc are subject to terms and conditions set out in the contract. Bondloc warrants only that its product will meet those specifications designated as such herein or in other publications. All other information supplied by Bondloc is considered accurate but are furnished upon the express condition the customer shall make its own assessment to determine the product's suitability for a particular purpose. Bondloc makes no other warranty, either express or implied, including those regarding such other information, the data upon which the same is based, or the results to be obtained from the use thereof; that any product shall be merchantable or fit for any particular purpose; or that the use of such other information or product will not infringe any patent.