

## **Bondloc B7765 PTFE Dry Film**

### **PRODUCT DESCRIPTION**

B7765 is a multi-purpose, food grade PTFE dry film for light lubrication. Non-toxic PTFE dry film for use as a dry anti-stick film or light lubrication of links, pins, chutes and slides etc. Operating in food/ clean environments.

### **APPLICATIONS**

For dry lubrication of sliding parts, especially where oils, greases and similar agents cause soiling. For metals, plastics and rubber. Film thickness of 10µm allows for use even with the very fine tolerances in precision engineering. Can also be used as separation agent e.g. in the plastic processing industry. For sliding roof and seat rails, door hinges and locks, sliding doors, tilting window mechanisms, window locks, furniture hinges, drawer runners, ball bearings and electrical switches.

### **USEFUL NOTES**

- Non soiling
- Anti-friction coating
- For metals, plastics and rubber
- Resistant to water, petrol, oils, alkalis and acids.

### **INSTRUCTIONS FOR USE**

Spray onto the surface from a distance of 20-30 cm. For more detailed application use the extension tube. For best results on moving parts, apply lightly whilst parts are in motion to ensure an even application. Wipe excess off with a cloth. Drying time 5-10 minutes.

### **TECHNICAL FEATURES**

Appearance (applied)	Colourless, dry film
Base type	PTFE
Propellant	Hydrocarbon
Solvent	Blend of hydrocarbon and alcohol
Temperature range	-200°C to 270°C

### **STORAGE**

Storage temperature should be kept below 50°C. Storage area should be out of direct sunlight.

### **HEALTH & SAFETY**

This technical information sheet does not constitute a Material Safety Data Sheet (MSDS). Before using this product ensure you have read and fully understood B3298 MSDS. Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on an open flame or any incandescent material. Keep away from sources of ignition.

### **PRESENTATION**

Aerosol.....400ml