

Bondloc B7766 PTFE Lubricant

PRODUCT DESCRIPTION

B7766 is a high performance maintenance lubricant with PTFE. Designed to provide excellent lubrication, penetration and protection in the widest range of applications. It is clean, non-toxic, highly penetrating and free from chlorinated solvents. Reduces friction in all moving parts including chains, threaded components, sliding surfaces etc.

APPLICATIONS

USEFUL NOTES

- Temperature range -55°C to 250°C
- Outstanding EP performance (315kg weld load)
- Ultra-high performance universal maintenance lubricant
- Clean and non-toxic lubricating film
- Contains PTFE as a solid lubricant – reduces friction

INSTRUCTIONS FOR USE

Shake aerosol well before use. Apply from a distance of 15-30cm (6-12 inches)

B7766 can be sprayed from any angle due to the 360° valve technology, enabling easy application of the product. It is recommended that compatibility with painted and coated surfaces, plastics and rubbers be tested prior to use.

TECHNICAL FEATURES

| | |
|----------------|-------------------|
| Physical state | 400ml aerosol |
| Appearance | Almost colourless |
| Base type | Synthetic ester |
| Solvent | Hydrocarbon |
| Solids | PTFE |

STORAGE

Store in a cool area out of direct sunlight. Shelf life >12 months at 20°C

HEALTH & SAFETY

This technical information sheet does not constitute a Material Safety Data Sheet (MSDS). Before using this product ensure you have read and fully understood B3298 MSDS. Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn even after use. Do not spray onto naked flame or any incandescent material. Keep away from sources of ignition.

PRESENTATION

Aerosol.....400ml