



Technical Data Sheet

Bondloc B773 Aluminium Anti-Seize

PRODUCT DESCRIPTION

B773 is an effective pre-assembly compound and thread lubricant which can be used where the exclusion of copper is required, for example where copper can be electrically or chemically active. It is particularly recommended for use with chemicals that can react with copper, such as ammonia in refrigerators, is likely to be experienced.

APPLICATIONS

B773 is recommended for use with chemicals that can react with copper. B773 can be used on threaded part, reduces torque, prevents seizing and galling.

INSTRUCTIONS FOR USE

Clean mating surfaces for application. Note when grinding or wire brushing use a dust mask. Dust from cleaning threads may contain metal compounds. Inhalation may cause lung injury or other harm. Apply a thin coating to threads, flats, nuts and bolts. Assemble and wipe away any excess.

PRODUCT DISCLAIMER

Bondloc offers this Technical Data Sheet ("TDS") for descriptive and informational use only. It is not a warranty, a contract or a substitute for expert or professional advice. Please also see the local product Safety Data Sheet for health and safety considerations. The statements, technical information, data, and recommendations contained in this TDS are provided 'AS IS' and are not warranted or guaranteed in any way. They represent typical results for the products and are based on Bondloc's research only. Since the conditions and methods of use of the products are beyond our control, Bondloc expressly disclaims any and all liability and damages of whatever kind or nature that may arise from any use of the products, the results therefrom, or reliance on the information contained herein. This TDS is one of several tools that may be used to help you find the product best suited for your needs. It is used at your own risk, and by using it, you are knowingly accepting and assuming any and all risks associated with its use and recommendations. BUYERS AND USERS ASSUME ALL RESPONSIBILITY AND LIABILITY FOR ANY AND ALL LOSS OR DAMAGE OF WHATEVER KIND OR NATURE ARISING FROM OR RELATED TO THE HANDLING OR USE OF BONDLOC'S PRODUCTS. The performance of the product, its shelf life, and application characteristics will depend on many variables, including but not limited to the kind of materials to which the product will be applied, the environment in which the product is stored and/or applied, and the equipment used for the application, among other things. Any change in any of these variables can affect the product's performance. You are responsible to test the suitability of any product in advance for any intended use or application. Bondloc does not guarantee the reliability, completeness, use, or function of the statements, technical information, data, and recommendations contained in this TDS.

Bondloc UK Ltd.
Units 1 & 2
Bewdley Business Park
Bewdley, Worcestershire
DY12 2TZ, UK

+44 (0) 1299 269 269
sales@bondloc.co.uk

TECHNICAL FEATURES

Colour	Silver
Base	Bentone (infusible)
Solubility	Insoluble in water
Temperature Range	Any sub-zero - 1100°C
Flash Point of Base Oil	250°C

HEALTH & SAFETY

This technical information sheet does not constitute a Safety Data Sheet (SDS). Before using this product ensure you have read and fully understood this products SDS.

PACKAGING FORMAT

Tin.....500g
Powercan.....200ml

