

Technical Data Sheet

B7771BZ Bright Zinc Galvanising Spray

PRODUCT DESCRIPTION

B7771BZ Bright Zinc Galvanizing Spray is a zinc/aluminum based coating designed for anti-corrosive and decorative applications on galvanized steel, steel, iron, aluminum, welds and most other metals. Contains high purity of powdered Zinc Metal (99%) and Aluminum flake for excellent electrochemical protection.

USEFUL NOTES

- Provides a bright, decorative and long lasting anti-corrosive finish.
- Dried coat contains ~60% metal content.
- Excellent adhesion to cleaned, prepared metallic surfaces.
- · Excellent flexibility.
- Quick drying, no secondary curing required.
- Suitable for exterior applications.
- Excellent resistance to salt spray and weathering.
- Suitable for welding through.

No chlorinated solvents. Totally lead and chromate free.

APPLICATIONS

For general use in all situations where clean and degreased metal surfaces need to be protected against corrosion:

- Repair of galvanized parts
- Trailers Railroad equipment
- Transmission towers Transformers
- Storage tanks Fencing
- Offshore oil rigs Sub-station equipment
- Farm equipment Roof/Stair guard rails

INSTRUCTIONS FOR USE

Ensure surface to be coated is clean, dry and free from grease. Shake can until agitator ball can be heard and then for a further 1 to 2 minutes. Spray from 25-30 cm, building up layers in light coats. Allow a minimum of 10 minutes drying time.

Bondloc UK Ltd. Units 1 & 2 Bewdley Business Park Bewdley, Worcestershire DY12 2TZ, UK

+44 (0) 1299 269 269 sales@bondloc.co.uk

TECHNICAL FEATURES

Appearance	Metallic silver liquid
Flammability	Extremely flammable, flash point below -20°C
Service Temperature	Designed for use at ambient temperatures. 15-24°C
Odour	Strong organic solvent
Contents / Composition	A solvent based solution of acrylic resin with micronized zinc and aluminum metal, propelled by butane/isobutane and propane.
Operating Temperature	Up to 100°C
Storage	8 °C to 20 °C
Touch Dry	10-15 minutes
Full Cure	24 hours

HEALTH & SAFETY

This technical information sheet does not constitute a Safety Data Sheet (SDS). Before using this product ensure you have read and fully understood this products SDS.

STORAGE

Store product in a dry location and out of direct sunlight.

PACKAGING

Aerosol Can - 500ml 6 cans per box



Revision date: 15/09/2023



Technical Data Sheet

Supersedes date: 22/01/2020

B7771BZ Bright Zinc Galvanising Spray

PRODUCT DISCLAIMER

Bondloc offers this Technical Data Sheet ("TDS") for descriptive and informational use only. It is not a warranty, a contract or a substitute for expert or professional advice. Please also see the local product Safety Data Sheet for health and safety considerations. The statements, technical information, data, and recommendations contained in this TDS are provided 'AS IS' and are not warranted or guaranteed in any way. They represent typical results for the products and are based on Bondloc's research only. Since the conditions and methods of use of the products are beyond our control, Bondloc expressly disclaims any and all liability and damages of whatever kind or nature that may arise from any use of the products, the results therefrom, or reliance on the information contained herein. This TDS is one of several tools that may be used to help you find the product best suited for your needs. It is used at your own risk, and by using it, you are knowingly accepting and assuming any and all risks associated with its use and recommendations. BUYERS AND USERS ASSUME ALL RESPONSIBILITY AND LIABILITY FOR ANY AND ALL LOSS OR DAMAGE OF WHATEVER KIND OR NATURE ARISING FROM OR RELATED TO THE HANDLING OR USE OF BONDLOC'S PRODUCTS. The performance of the product, its shelf life, and application characteristics will depend on many variables, including but not limited to the kind of materials to which the product will be applied, the environment in which the product is stored and/or applied, and the equipment used for the application, among other things. Any change in any of these variables can affect the product's performance. You are responsible to test the suitability of any product in advance for any intended use or application. Bondloc does not guarantee the reliability, completeness, use, or function of the statements, technical information, data, and recommendations contained in this TDS.

Revision: 2

Bondloc UK Ltd. Units 1 & 2 Bewdley Business Park Bewdley, Worcestershire DY12 2TZ, UK



