



Technical Data Sheet

Bondloc B7775 Copper Anti-Seize

PRODUCT DESCRIPTION

B7775 is a high temperature lubricant providing outstanding overall metal protection against heat, rust, seizure and corrosion. Resistance to water and acids is high and it will not burn off under extreme stress.

APPLICATIONS

B7775 can be used on threaded components, pins, valve stems in a range of materials including austenitic stainless steel. Used on brake calipers and the back of brake pads it will help eliminate brake squeal.

USEFUL NOTES

- Effective up to 1100°C
- Water and acid resistant
- Use on a wide range of metals.
- Prevents seizure of threaded parts
- Will not burn or wash off.
- Eliminates brake squeal.
- Assists in assembly and disassembly of components.

INSTRUCTIONS FOR USE

Shake can well before use. Spray from 1530cm wipe off excess.

Do not apply to friction materials and pads.

STORAGE

Storage temperature should be kept below 50°C. Storage area should be out of direct sunlight.

TECHNICAL FEATURES

Appearance	Copper coloured grease
Odour	Oily solvent
Contents	Blend of copper paste, calcium grease, mineral oils and hydrocarbon solvents and propellants
Solubility	Insoluble in water
Storage	Below 50°C
Flash Point	-60°C
Temperature Range	-150°C to +1100°C

HEALTH & SAFETY

This technical information sheet does not constitute a Safety Data Sheet (SDS). Before using this product ensure you have read and fully understood this products SDS.

PACKAGING FORMAT

Aerosol Can.....500ml

Bondloc UK Ltd.
 Units 1 & 2
 Bewdley Business Park
 Bewdley, Worcestershire
 DY12 2TZ, UK

+44 (0) 1299 269 269
 sales@bondloc.co.uk





Technical Data Sheet

Bondloc B7775 Copper Anti-Seize

PRODUCT DISCLAIMER

Bondloc offers this Technical Data Sheet ("TDS") for descriptive and informational use only. It is not a warranty, a contract or a substitute for expert or professional advice. Please also see the local product Safety Data Sheet for health and safety considerations. The statements, technical information, data, and recommendations contained in this TDS are provided 'AS IS' and are not warranted or guaranteed in any way. They represent typical results for the products and are based on Bondloc's research only. Since the conditions and methods of use of the products are beyond our control, Bondloc expressly disclaims any and all liability and damages of whatever kind or nature that may arise from any use of the products, the results therefrom, or reliance on the information contained herein. This TDS is one of several tools that may be used to help you find the product best suited for your needs. It is used at your own risk, and by using it, you are knowingly accepting and assuming any and all risks associated with its use and recommendations. BUYERS AND USERS ASSUME ALL RESPONSIBILITY AND LIABILITY FOR ANY AND ALL LOSS OR DAMAGE OF WHATEVER KIND OR NATURE ARISING FROM OR RELATED TO THE HANDLING OR USE OF BONDLOC'S PRODUCTS. The performance of the product, its shelf life, and application characteristics will depend on many variables, including but not limited to the kind of materials to which the product will be applied, the environment in which the product is stored and/or applied, and the equipment used for the application, among other things. Any change in any of these variables can affect the product's performance. You are responsible to test the suitability of any product in advance for any intended use or application. Bondloc does not guarantee the reliability, completeness, use, or function of the statements, technical information, data, and recommendations contained in this TDS.

Bondloc UK Ltd.
Units 1 & 2
Bewdley Business Park
Bewdley, Worcestershire
DY12 2TZ, UK

+44 (0) 1299 269 269
sales@bondloc.co.uk

