

Technical Data Sheet

Bondloc B7776 – Chain & Cable Lubricant

Revised 03.08.10



Bondloc B7776 Chain & Cable Lubricant

PRODUCT DESCRIPTION

B7776 is a heavy duty, molybdenum disulphide reinforced lubricant which penetrates deeply into drive chains and wire ropes to give long lasting lubrication, preventing corrosion, wear and chain elongation, it gives outstanding performance under extreme load and is resistant to fling off.

APPLICATIONS

B7776 can be used on chain blocks, drive chains, fork lift chains and wire ropes.

USEFUL HINTS

- Use on chain blocks, drive chains, fork lift chains and wire ropes.
- Extreme pressure additives for heavy loads
- Excellent lubrication properties
- Resistant to flinging off
- Penetrates deeply
- High resistance to wash off

INSTRUCTIONS FOR USE

Shake can well before use. Spray from 15-30cm on to surface to be treated, allow to penetrate. After use invert can and spray to clear nozzle

STORAGE

Storage temperature should be kept below 50°C. Storage area should be out of direct sunlight.

TECHNICAL FEATURES

Appearance	Brown foaming spray
Odour	Oily solvent
Contents	Blend of mineral oils, molybdenum disulphide, extreme pressure and dewatering additives, solvent and hydrocarbon propellants.
Solubility	Insoluble in water
Storage	Below 50°C
Flash Point	< 0°C
Relative Density	0.722
Temperature range	-10°C - 180°C

HEALTH & SAFETY IN USE

Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on to an open flame or any incandescent material. Keep away from sources of ignition. This technical information sheet for does not constitute a Material Safety Data Sheet (MSDS). Before using this product ensure you have read and fully understand the MSDS.

PRESENTATION

Aerosol.....400ml

PRECAUTIONS: This product and the auxiliary materials normally combined with it are capable of producing adverse health effects ranging from minor skin irritation to serious systemic effects. None of these materials should be used, stored, or transported until the handling precautions and recommendations as stated in the Material Safety Data Sheets (MSDS) for this and all other products being used are understood by all persons who will work with the product. Warranty: All products purchased from or supplied by Bondloc are subject to terms and conditions set out in the contract. Bondloc warrants only that its product will meet those specifications designated as such herein or in other publications. All other information supplied by Bondloc is considered accurate but are furnished upon the express condition the customer shall make its own assessment to determine the product's suitability for a particular purpose. Bondloc makes no other warranty, either express or implied, including those regarding such other information, the data upon which the same is based, or the results to be obtained from the use thereof; that any product shall be merchantable or fit for any particular purpose; or that the use of such other information or product will not infringe any patent.