



# Technical Data Sheet

## Bondloc B7778 Cut & Tap Fluid

### PRODUCT DESCRIPTION

A ready to use cutting and tapping fluid specially formulated to improve tool performance and extend tool life. It contains additives to prevent pitting, galling, and metal seizures. B7778 reduces heat build-up and incorporates corrosion inhibitors.

### APPLICATIONS

B7778 can be used for cutting, tapping, reaming and turning. It is suitable for use on aluminium and steel.

### USEFUL NOTES

- For cutting, tapping, reaming, and turning
- Extreme pressure additives
- High pressure discharge to aid penetration.
- Prolongs tool life and improves machined finish.
- Reduced heat build up
- Incorporates corrosion inhibitors.
- Chlorine free

### INSTRUCTIONS FOR USE

Shake can well before use. Spray tool area to be treated, repeat if necessary.

### STORAGE

Storage temperature should be kept below 50°C. Storage area should be out of direct sunlight.

### TECHNICAL FEATURES

Appearance	Brown liquid
Odour	Sweet solvent
Contents	Blend of highly refined paraffinic mineral oils, white spirit, extreme pressure additives, corrosion inhibitors, hydrocarbon solvents and propellants
Solubility	Insoluble in water
Storage	Below 50°C
Flash Point	- 40°C
Relative Density	0.840
Temperature Range	For use at ambient temperatures

### HEALTH & SAFETY

This technical information sheet does not constitute a Safety Data Sheet (SDS). Before using this product ensure you have read and fully understood this products SDS.

### PACKAGING FORMAT

Aerosol Can.....400ml

Bondloc UK Ltd.  
Units 1 & 2  
Bewdley Business Park  
Bewdley, Worcestershire  
DY12 2TZ, UK

+44 (0) 1299 269 269  
sales@bondloc.co.uk





# Technical Data Sheet

## Bondloc B7778 Cut & Tap Fluid

### PRODUCT DISCLAIMER

Bondloc offers this Technical Data Sheet ("TDS") for descriptive and informational use only. It is not a warranty, a contract or a substitute for expert or professional advice. Please also see the local product Safety Data Sheet for health and safety considerations. The statements, technical information, data, and recommendations contained in this TDS are provided 'AS IS' and are not warranted or guaranteed in any way. They represent typical results for the products and are based on Bondloc's research only. Since the conditions and methods of use of the products are beyond our control, Bondloc expressly disclaims any and all liability and damages of whatever kind or nature that may arise from any use of the products, the results therefrom, or reliance on the information contained herein. This TDS is one of several tools that may be used to help you find the product best suited for your needs. It is used at your own risk, and by using it, you are knowingly accepting and assuming any and all risks associated with its use and recommendations. BUYERS AND USERS ASSUME ALL RESPONSIBILITY AND LIABILITY FOR ANY AND ALL LOSS OR DAMAGE OF WHATEVER KIND OR NATURE ARISING FROM OR RELATED TO THE HANDLING OR USE OF BONDLOC'S PRODUCTS. The performance of the product, its shelf life, and application characteristics will depend on many variables, including but not limited to the kind of materials to which the product will be applied, the environment in which the product is stored and/or applied, and the equipment used for the application, among other things. Any change in any of these variables can affect the product's performance. You are responsible to test the suitability of any product in advance for any intended use or application. Bondloc does not guarantee the reliability, completeness, use, or function of the statements, technical information, data, and recommendations contained in this TDS.

---

Bondloc UK Ltd.  
Units 1 & 2  
Bewdley Business Park  
Bewdley, Worcestershire  
DY12 2TZ, UK

---

+44 (0) 1299 269 269  
sales@bondloc.co.uk

---

