

## **Technical Data Sheet**

### Bondloc B3400 Acrylic/PMMA Bonder

#### PRODUCT DESCRIPTION

B3400 is a 10:1 ratio, two component, reactive acrylic adhesive. Designed to be high strength and transparent, B3400 is recommended for applications where excellent clarity is needed. Suitable applications include aquarium manufacture and repair, museum quality cases, sign making and plastic fabrication industries.

#### **APPLICATIONS**

B3400 is suitable for bonding polyester, polycarbonate, cellulose acetate butyrate, acrylics and is especially designed for use on clear acrylic/PMMA.

#### **USEFUL HINTS/NOTES**

- High strength and excellent clarity
- Supplied in cartridge for ease of use
- 14-17 minute working life

#### **INSTRUCTIONS FOR USE**

- Some surface preparation maybe required. Ensure the surfaces to be bonded are clean of oil, dust, dirt and grease
- Load cartridge into dispensing gun, ensure both A/B are free flowing.
- Secure the mixer tip to cartridge and place into applicator gun. Dispense and discard the first portion of the mixed adhesive.
- Apply the adhesive, mate the substrates within the work life of the adhesive: 14-17 minutes.
- The bonded surfaces should be held in place or clamped for at least 2 hours.

#### **TECHNICAL FEATURES**

	Adhesive	Activator
Colour	Clear	Clear
Viscosity	3000 cps	400 cps
Shelf Life @ 20°C	12 months	
Storage	10 - 23°C	
Working Time	14 - 17 mins	
Full Cure Time @	72 hours	
Time to Handling	110 – 125 mins	

#### TYPICAL BOND CHARACTERISTICS

Property	Typical value
Tensile Strength	15 - 17 MPa
Tensile Elongation	<5%
Gap Fill	0.1 – 2 mm

#### **STORAGE**

Shelf life up to 12 months when stored unopened at the recommended temperature between 10 - 23°C. Exposure to temperatures above 23°C will shorten shelf life. Do not freeze. Allow product to reach room temperature (18 - 25°C) before use

#### **HEALTH & SAFETY**

This technical information sheet does not constitute a Safety Data Sheet (SDS). Before using this product ensure you have read and fully understood this products SDS

#### **PACKAGING FORMAT**

Cartridge......50ml, 490ml

Bondloc UK Ltd. Units 1 & 2 Bewdley Business Park Bewdley, Worcestershire DY12 2TZ, UK

+44 (0) 1299 269 269 sales@bondloc.co.uk



Revision date: 09/10/2023 Revision: 2



# **Technical Data Sheet**

Supersedes date: 20/11/2017

Bondloc B3400 Acrylic/PMMA Bonder

#### **PRODUCT DISCLAIMER**

Bondloc offers this Technical Data Sheet ("TDS") for descriptive and informational use only. It is not a warranty, a contract or a substitute for expert or professional advice. Please also see the local product Safety Data Sheet for health and safety considerations. The statements, technical information, data, and recommendations contained in this TDS are provided 'AS IS' and are not warranted or guaranteed in any way. They represent typical results for the products and are based on Bondloc's research only. Since the conditions and methods of use of the products are beyond our control, Bondloc expressly disclaims any and all liability and damages of whatever kind or nature that may arise from any use of the products, the results therefrom, or reliance on the information contained herein. This TDS is one of several tools that may be used to help you find the product best suited for your needs. It is used at your own risk, and by using it, you are knowingly accepting and assuming any and all risks associated with its use and recommendations. BUYERS AND USERS ASSUME ALL RESPONSIBILITY AND LIABILITY FOR ANY AND ALL LOSS OR DAMAGE OF WHATEVER KIND OR NATURE ARISING FROM OR RELATED TO THE HANDLING OR USE OF BONDLOC'S PRODUCTS. The performance of the product, its shelf life, and application characteristics will depend on many variables, including but not limited to the kind of materials to which the product will be applied, the environment in which the product is stored and/or applied, and the equipment used for the application, among other things. Any change in any of these variables can affect the product's performance. You are responsible to test the suitability of any product in advance for any intended use or application. Bondloc does not guarantee the reliability, completeness, use, or function of the statements, technical information, data, and recommendations contained in this TDS.

Bondloc UK Ltd. Units 1 & 2 Bewdley Business Park Bewdley, Worcestershire DY12 2TZ, UK

+44 (0) 1299 269 269 sales@bondloc.co.uk

